



SPRAYSTREAM	SPRAYSTREAM Mini	SPRAYSTREAM Mini-Trolley	SPRAYSTREAM S2.2 Mobiler Trolley	SPRAYSTREAM S2.2 Cart Single	SPRAYSTREAM S2.2 Plattform	SPRAYSTREAM S2.2 Autark	SPRAYSTREAM S4.0	SPRAYSTREAM S4.0 AUTARK	SPRAYSTREAM S7.5/S11.0/S15.0	SPRAYSTREAM S7.5 AUTARK	SPRAYSTREAM S7.5 POWER	SPRAYSTREAM S7.5 TOWER	SPRAYSTREAM S7.5 Vertikaltank	SPRAYSTREAM S18.5/S30.0	SPRAYSTREAM S75.0	TANK-CONTAINER 6 cbm
Ausführung	Mobiles Standgerät	Mobiler Trolley	Mobiler Trolley	Mobile Staubbinde- maschine	Teleskopierbarer Edelstahlmast	Autarker Anhänger mit 2.500-L-Tank und Generator	Mobile Staubbinde- maschine	Autarke Staub- bindemaschine mit 1.250-L-Tank	Staubbinde- maschinen Standard (20 bar)	Autarker Anhänger mit 2.000-L-Tank	Teilautarker Anhänger mit Generator	Stationäre Staub- bindemaschine 4 m Höhe	Staubbinde- maschine mit 3.000-L-Tank	Mobile Staubbinde- maschine	Mobile Staubbinde- maschine	Mobiler Tank- Container
Wurfweite	10 m	15 m	25 m	25 m	30 m	30 m	35 m	35 m	50 – 70 m	50 m	50 m	60 m	55 m	80 m - 100 m	150 m	–
Länge/Breite/Höhe (mm)	500/360/635	1.350/600/900	1.350/1.100/1.550	1.350/1.200/1.950	1.250/1.100/2.700	5.500/1.700/3.100	1.450/1.600/2.000	2.900/1.400/2.900	1.550/1.600/2.350	5.300/2.450/3.100	4.700/1.820/3.250	1.550/1.600/6.500	1.550/1.600/4.500	1.800/1.600/2.350	3.000/2.900/2.700	2.438/2.200/2.260
Gewicht (kg)	15	60	210	175 – 200	285	1.100 – 1.350	350	700	470/500/530	2.200	2.000	900	900	570/600	2.500	600
Elektrische Leistung:																
Pumpe (kW)	–	0,75	1,5	1,5–2,2	1,5–2,2	1,1	1,5–3	1,5	4	4	5,5	5,5	5,5	5,5	11	–
Totalbelastung (A)	–	7	6 – 9	9	9	6 – 8	16	16	25/28/39	25	28	25	25	49/56	–	–
Stromanschluss (A)	1x230 VAC	1x230 VAC	16	16	16	16	1x230 VAC – 16 A	1x230 VAC – 16 A	32/32/63	32	32	32	32	63	125	1 x 230 VAC
Minim. Leistung Generator (KVA)	–	3	8	10	10	–	12	10	18/25/35	–	–	18	18	45/60	–	–
Hydraulische Leistung:																
Wasserdruck Booster-Pumpe (bar)	–	100	80	20–80	20 – 80	20	20	20	20	20	20	20	20	20	20	–
Wasserdurchsatz (l/h)	10–60	10–60	190 – 390	400–900	400–900	400–900	600–1.200	600–1.200	2.700	1.300–2.700	1.800–3.600	3.600	2.700	4.500/5.400	6.000–12.000	–